
	Getting Started in Terra: Importing Reads, Metadata, Workflows, and More	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

1. PURPOSE/SCOPE

To standardize the process of uploading next generation sequencing (NGS) data from local storage or the Sequencing Reads Archive (SRA) and creating and uploading a results metadata table using the online Terra platform for downstream Theiagen workflow analysis. Additional instructions are provided in the appendices for importing workflows and adding workspace data elements and files. Acceptable NGS data types include Illumina, Oxford Nanopore Technology (ONT), ClearLabs, and FASTA file formats. Read the comprehensive workflow documentation [here](#).

2. TABLE OF CONTENTS

1. PURPOSE/SCOPE.....	1
2. TABLE OF CONTENTS	1
3. REQUIRED RESOURCES	2
4. RELATED DOCUMENTS.....	2
5. PROCEDURE	2
5.1 IMPORTING LOCAL RAW READS	2
5.2 IMPORTING SAMPLE METADATA (TSV FILE) AFTER CREATING COLLECTION OF READ FILES ..	3
5.3 IMPORTING SAMPLE METADATA (TSV FILE) WITHOUT CREATING A READ COLLECTION	5
5.4 IMPORTING RAW READS USING SRA_FETCH	6
5.5 IMPORTING RAW READS FROM BASESPACE	8
6. QUALITY RECORDS	8
7. TROUBLESHOOTING	9
8. LIMITATIONS	9
9. REFERENCES	9
10. REVISION HISTORY	9
10. APPENDICES	10
10.1 CREATING A METADATA FILE (TSV FILE)	10
10.2 IMPORTING A WORKFLOW FROM DOCKSTORE	12
10.3 ADDING AND UPDATING WORKSPACE DATA ELEMENTS AND FILES	15
10.4 REFERENCING A WORKSPACE FILE IN A WORKFLOW	17

	Getting Started in Terra: Importing Reads, Metadata, Workflows, and More	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

3. REQUIRED RESOURCES

- Computer
- Internet connection: at least 10 and 5Mbps for download and upload speeds, respectively
- Internet browser
 - Google Chrome, Firefox, or Edge
- Google account
- Terra account, linked to Google account

IMPORTANT NOTES

Metadata column headers and workflow input text indicated in **gray** in this SOP are customizable; **black** is required text.

4. RELATED DOCUMENTS

Document Number	Document Name
TG-TER-04	Linking BaseSpace and Importing BaseSpace Reads to Terra Workspace

5. PROCEDURE

5.1 IMPORTING LOCAL RAW READS

1. **Sign in** to <https://app.terra.bio/> using a Gmail account and Google Authentication (Figure 1)
2. Click on the **hamburger icon** in the top left and navigate to **Workspaces** (Figure 2)
3. **Open the workspace** designated for analysis
4. In the data tab, click **Import data** and select **Open data uploader** (Figure 3)
5. For new data sets, click **Create a New Collection** (Figure 4)
 - a. *The following nomenclature may be useful: YYYYMMDD_# (do not include spaces)*
6. Click **Upload** or **drag and drop** raw sequencing reads into the data table
7. When upload is complete, files will populate on this page with **file names hyperlinked** to their corresponding Google Bucket location (Figure 5)
8. Continue to [section 5.2](#) to upload sample metadata.





Figure 1

	<h1>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h1>	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1




Figure 2




Figure 3




Figure 4





Figure 5

5.2 IMPORTING SAMPLE METADATA (TSV FILE) AFTER CREATING COLLECTION OF READ FILES

1. Once files have successfully uploaded, click [Next](#) (Figure 5)
2. Import the associated sample metadata file or drag and drop from file explorer (Figure 6)
 - a. See [appendix 10.1](#) to create a sample metadata file

	<h2>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h2>	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1




Figure 6

b. Alternatively, use the auto-generation option and carefully review

AUTOGENERATE TABLE FOR SINGLE OR PAIRED END SEQUENCING

i. When using this function, the collection name should be the desired table name

3. Click **create table** (Figure 7)





Figure 7

4. View the uploaded read data and metadata in the Terra data table by clicking **View the...table in the workspace** at the bottom of the screen
5. In the data tab, all read files and metadata are now populated for each sample in the associated table (e.g. *illumina_pe_specimen* table)
 - a. Open the data table by clicking on the table name in the sidebar (Figure 8)



	illumina_pe_specimen_id	read1	read2	run_id
<input type="checkbox"/>	Sample_01	13_S13_L001_R1_001.fastq.gz	13_S13_L001_R2_001.fastq.gz	training_data
<input type="checkbox"/>	Sample_02	15_S15_L001_R1_001.fastq.gz	15_S15_L001_R2_001.fastq.gz	training_data
<input type="checkbox"/>	Sample_03	17_S17_L001_R1_001.fastq.gz	17_S17_L001_R2_001.fastq.gz	training_data
<input type="checkbox"/>	Sample_04	18_S18_L001_R1_001.fastq.gz	18_S18_L001_R2_001.fastq.gz	training_data

Figure 8

5.3 IMPORTING SAMPLE METADATA (TSV FILE) WITHOUT CREATING A READ COLLECTION

- To upload the metadata file to Terra, return to the [Terra workspace](#) containing data of interest
- In the [data](#) tab, click [import data](#), and [upload TSV](#) (Figure)
- In the pop-up window, [drag and drop](#) the file in the gray box or [click to select](#) the metadata file, then click [start import job](#) (Figure 10)
 - See [appendix 10.1](#) to create a sample metadata file
 - If adding metadata to samples in an existing data table, ensure the data table name indicated in the TSV file in cell A1 contains the same data table name listed in Terra (e.g. `[DATATABLE_NAME]_id`)




Figure 9





Figure 10

- All samples and metadata should now be populated in the corresponding Terra data table (Figure 8)

	Getting Started in Terra: Importing Reads, Metadata, Workflows, and More	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

5.4 IMPORTING RAW READS USING SRA_FETCH

1. Navigate to the Terra workspace that will be used to import reads
2. In the data tab, click on **import data** and **upload TSV** (Figure)
3. Import a TSV file containing the table of SRA accession numbers for desired samples: **select** or **drag and drop** the file, then click **start import job** (Figure)
 - a. A template TSV file can be downloaded from this pop-up; follow [appendix 10.1](#) to create a metadata/TSV file (for SRA Fetch, the TSV file does not need read1 or read2 columns, only sra accession) (Figure 4)




Figure 11




Figure 12

kleb_training_id	sra_accession	acquisition	hospital	month
INF004	ERR1023740	HA	A	4
INF026	ERR1023759	HA	A	4
INF029	ERR1023762	Nosocomial	A	4
INF055	ERR1023788	Nosocomial	C	5
INF064	ERR1023715	HA	A	5
INF074	ERR1008633	Nosocomial	A	5

Figure 13

4. In the workflows tab, click **SRA_Fetch_PHB**
 - a. Refer to [appendix 10.2](#) for how to import a workflow into a workspace



SRA_Fetch_PHB

Version: **v3.1.1** **a**

Source: github.com/theiagen/public_health_bioinformatics/SRA_Fetch_PHB:v3.1.1

Synopsis:

No documentation provided

☐ Run workflow with inputs defined by file paths
☒ **Run workflow(s) with inputs defined by data table** **b**

Step 2

c **EIEC_Samples** **d** **Select Data**

Runtime options: **i**

Set cost threshold per workflow **i**


\$ Example: 1.00

Learn more about how Terra implements cost thresholds

☐ Use call caching **i**
☐ Use reference disks **i**
☒ **Ignore empty outputs** **i**
☐ Delete intermediate outputs **i**
☐ Resource monitoring **i**

Figure 14

- Set the workflow **version** to the latest version, or the workflow version used for internal validations (Fig 14, a)
- Choose the second bullet to **run workflow(s) with inputs defined by data table** (Fig 14, b)
- Select the sample table to use under **select data table** (Fig 14, c)
 - Do not choose the "set" table version
- Click **select data** (Fig 14, d) and **mark the checkboxes** to specify which sample reads to import (Fig 15)



Select Data

☒ Choose specific EIEC_Samples to process
☐ Choose existing sets of EIEC_Samples


Select EIEC_Samples to process **Settings** 0 rows selected **Advanced Search** Search

<input type="checkbox"/>	EIEC_Sa...	Expected_Serotypes	ectyper_predicted_serotype	ecty...
<input type="checkbox"/>	Sample_1	O143:H26	O143:-	Samr
<input type="checkbox"/>	Sample_10	2a	O13/O135:H14	Samr
<input type="checkbox"/>	Sample_2	O124:H30	O124/O164:H30	Samr
<input type="checkbox"/>	Sample_3	O144:H25	O144:H25	Samr
<input type="checkbox"/>	Sample_4	O143:H26	O143:-	Samr
<input type="checkbox"/>	Sample_5	O143:H26	O143:-	Samr


1 - 10 of 10 **1** Items per page: 100

Cancel OK

Figure 15


	Getting Started in Terra: Importing Reads, Metadata, Workflows, and More	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

9. Set the first input setting to `this.sra_accession`, where `sra_accession` is the TSV file column name containing SRA numbers (Figure)
10. In the outputs tab, click `use defaults` (Error! Reference source not found.) and `save` the workflow
11. Then click `run analysis`, enter any comments if desired, and click `launch`
12. Fetched reads will be populated in the `read1` and `read2` columns of the data table



Task name ↓	Variable	Type	Attribute
fetch_sra_to_fastq	sra_accession	String	this.sra_accession
fetch_sra_to_fastq	cpus	Int	Optional
fetch_sra_to_fastq	disk_size	Int	Optional

Figure 16



Type	Input value	Use defaults
File	this.abricate_abaum_plasmid_tsv	{...}
String	this.abricate_abaum_plasmid_type_genes	{...}


Figure 17

5.5 IMPORTING RAW READS FROM BASESPACE

1. Command line steps are required for the initial setup between BaseSpace and Terra. Refer to the following sites for details on initial setup and the import process:
 - a. Theiagen's [BaseSpace Fetch Documentation](#)
 - b. Document TG-TER-04, Version 3

6. QUALITY RECORDS

- Raw read files
- Metadata results table
- Workspace elements and files

	Getting Started in Terra: Importing Reads, Metadata, Workflows, and More	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

7. TROUBLESHOOTING

- Terra data table column headers become available as workflow inputs when running workflows, search for them in workflow input dropdowns using the prefix [this](#). to filter
- For workspace data and files, search for them in workflow input dropdowns using the prefix [workspace](#).
- If the first cell in the metadata table does not end with [_id](#), an error message will prevent file import; adjust the metadata text in cell A1 and re-upload
- If any workflow, input, or output settings are entered incorrectly, the analysis will not run as expected; verify all settings are correct and re-launch analysis
- If analysis fails, navigate to the job history in the workspace and click on the job submission for details; for help resolving run failures, email support@theiagen.com

8. LIMITATIONS


N/A

9. REFERENCES

1. Libuit, Kevin G., Emma L. Doughty, James R. Otieno, Frank Ambrosio, Curtis J. Kapsak, Emily A. Smith, Sage M. Wright, et al. 2023. "Accelerating Bioinformatics Implementation in Public Health." Microbial Genomics 9 (7). <https://doi.org/10.1099/mgen.0.001051>
2. Theiagen Genomics [Public Health Bioinformatics Workflow Documentation](#)
3. Theiagen's [BaseSpace Fetch](#) and [SRA Fetch](#) workflow resource pages
4. Theiagen's [Docker Image and Reference Materials for SARS-CoV-2](#)
5. Theiagen's [Public Health Resources](#)

10. REVISION HISTORY

Revision	Version	Release Date
Document Creation	1	7/2023
Added internet speeds recommended for up/download, important notes, section 4.5, SRA metadata info in appendix 9.1, and appendix 9.3	2	9/2023
Formatting (Figure references and cross-references check), section 4.1 - 4.4 updates, inclusion of figure 15, appendix 10.1 updates	3	4/2024
Edits for version release, aligning with Terra interface, and formatting	4	5/2025
Edits for clarity, including a table of contents, additional figures, appendix on referencing workspace elements in a workflow, and figure reference and caption corrections	5	10/2025

	<h1>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h1>	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

10. APPENDICES

10.1 CREATING A METADATA FILE (TSV FILE)

1. Open the downloadable TSV template located in the Import Data/Upload TSV pop-up window (Figure 18)





Figure 18

2. Cell A1 must contain the following text: `[name]_id` (Figure 19)
 - a. Do not include spaces or characters other than hyphens (-) or underscores (_)
 - b. The data table name should contain text to indicate the project name (e.g. Cell A1 may read `HAI_id` to create a table for all HAI organisms)
3. Enter all *sample IDs* into column 1 below cell A1
4. Label column headers for desired metadata (do not include spaces or special characters) (Table 1)
 - a. Optional: enter `run_id` as a column header and the run ID for each sample in the column
 - b. Optional: add additional metadata columns and sample information, as needed

HAI_id	run_id	sample_matrix	county
2168435186	SEQ217	NP swab	Adams
2168435187	SEQ217	Buccal swab	Alameda

Table 1. Metadata setup with required and optional columns

	Getting Started in Terra: Importing Reads, Metadata, Workflows, and More	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

	A	B	C	D	E	F
1	HAI_id	read1	read2	run_id	sample_matrix	county
2	2168435186	100734_R1.fastq.gz	100734_R2.fastq.gz	SEQ217	NP swab	Adams
3	2168435187	100735_R1.fastq.gz	100735_R2.fastq.gz	SEQ217	Buccal swab	Alameda
4	2168435188	100735_R1.fastq.gz	100735_R2.fastq.gz	SEQ217	Buccal swab	Tulare
5	2168435189	100736_R1.fastq.gz	100736_R2.fastq.gz	SEQ217	NP swab	Gilpin

Figure 19

5. **For manually-uploaded reads** via the *Data Uploader*, include read columns (Figure 19)
 - a. For **paired-end** (PE) sequencing: **read1** and **read2**
 - b. For **single-end** (SE) sequencing: only **read1**
 - c. Use the **file name** as the value for this column (e.g. 100734_R1.fastq.gz) (Figure 20)

Upload New folder Delete			Analyze in Seqr Refresh	
<input type="checkbox"/>	Name	Size	Last modified	
<input type="checkbox"/>	100734_R1.fastq.gz	35 MB	Dec 1, 2024	
<input type="checkbox"/>	100734_R2.fastq.gz	42 MB	Dec 1, 2024	


Figure 20

6. **For SRA uploads:**
 - a. **Label the column header** for column 2 as **sra_accession**, or similar (Table 2)
 - b. Enter SRA accessions as the values for this column (e.g. SRR# or ERR#)

HAI_id	sra_accession	hospital	month	year	age	run_id
2168435186	ERR1023740	D	4	2013	30-39	SEQ217
4831845358	SRR11445892	A	2	2014	80-89	SEQ217
8415835241	ERR4087740	C	6	2013	60-69	SEQ217
6846813545	SRR11842392	A	3	2013	80-89	SEQ217

Table 2. Metadata table setup for SRA uploads.

7. In Excel, click **save as** and change the file type to **Text (Tab delimited)**.
8. Refer to [section 5.2](#) to import TSV files at the same time as creating new read collections (importing files locally) and [section 5.3](#) to import TSV files without creating read collections

	<h1>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h1>	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

10.2 IMPORTING A WORKFLOW FROM DOCKSTORE

1. In the *Terra workspace* of interest, navigate to the *workflows* tab and click *find a workflow* (Figure 21)
2. In the pop-up window, click *Dockstore.org* (Figure 22)
3. Workflows may be found through the search bar or by navigating through the organization if it is known
 - a. To find a Theiagen workflow
 - i. click *organizations* (Figure 23)
 - ii. In the search bar type *Theiagen* (Figure 23)
 - iii. Click on the *logo*, *view*, or *# collections*. (Figure 24)
 - iv. Click on the collection to see available workflows: *Public Health Bioinformatics (PHB)*
4. Find and *open the workflow* (workflow name listed at the end of the file path) (Figure 25)
5. Click *Terra* to launch the workflow in Terra (Figure 26)
6. Choose the *destination workspace* in the dropdown
7. Click *import* or *create a new workspace* (Figure 27)




Figure 21





Figure 22

	<h1>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h1>	
	Document TG-TER-03, Version 5	
	Date: 10/02/2025	Workflow Versions: PHB v3.1.1




Figure 23




Figure 24



Figure 25


	<h1>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h1>	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1



Figure 26





Figure 27

	<h1>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h1>	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

10.3 ADDING AND UPDATING WORKSPACE DATA ELEMENTS AND FILES

1. Navigate to the **Terra workspace** where analyses will be run
2. To upload local files:
 - a. Open the **workspace files** tab in the right-side panel of the workspace (Figure 28).
 - b. Click **upload**
 - c. Following upload, click the **clipboard** or **right click** on the file name to **copy link** (Figure 29)
3. To add workspace variables:
 - a. Click the **workspace data** tab at the bottom of the left-side panel (Figure 28)
 - b. Click **Edit** in the top menu (Figure 30)
 - c. Click **Add Variable** (Figure 30)
 - d. Click in the **key field** and **name the element** being added (Figure 31)
 - e. In the value field, choose **string** as the value type
 - f. Paste the file path copied above in step 2, or enter the desired file path (see below)
 - i. E.g. to add the Artic V4-1 primer bed file, the key **Artic_V4-1_primer_bed** may be used with the file path as the value (Figure 32)
4. Docker images and tags for TheiaCoV workflows should be included in workspace variables.
 - a. Ensure the docker images and dataset tags are aligned with versions used for internal validation procedures or are re-verified before use.
 - b. Available in the [Docker Image and Reference Materials for SARS-CoV-2](#)
 - c. All resources can be found on the [Theiagen Public Health Resources](#) page




Figure 28




Figure 29




Figure 30





Figure 31

Key	Value	Description
Artic_V3_primer_bed	V3_nCoV-2019.primer.bed	
Artic_V4-1_primer_bed	V4-1_nCoV-2021.primer.bed	
Artic_V4_primer_bed	V4_nCoV-2021.primer.bed	
FreyjaLineageMetadata	curated_lineages.json	Taken from Freyja_Workflows Demo Data
FreyjaUsherBarcodes	usher_barcodes.csv	Updated 8/3/23; taken from Freyja_Workflows D...
Freyja_ReferenceGenome	nCoV-2019.reference.fasta	MN908947.3
Midnight_primer_bed	Midnight_PrimerSARS-CoV-2.scheme.bed	
SWIFT_primer_bed	SWIFT_SARS-CoV-2.scheme.bed	Updated 2023-07-05

Figure 32

	<h1>Getting Started in Terra: Importing Reads, Metadata, Workflows, and More</h1>	
	Document TG-TER-03, Version 5	
	Date:	Workflow Versions:
	10/02/2025	PHB v3.1.1

10.4 REFERENCING A WORKSPACE FILE IN A WORKFLOW

When there is a workflow input that you may wish to reference regularly (e.g. a Kraken database or reference assembly file), you can indicate the file saved as a workspace element (see above section 10.3 for guidance on creating a workspace element).

1. Make sure the reference file you want to use is uploaded and stored as a workspace element by going to the Data tab of your workspace, scrolling down to the bottom to click where it says “Workspace data” (Figure 33).




Figure 33

2. Return to the Workflows tab and go to the variable that would require a workspace data element. Type “workspace.”--you will see all the workspace data elements you have saved appear in a dropdown. Continue typing or scroll to find the appropriate element for your workflow and select it (Figure 34).

Task name ↓	Variable	Type	Input value
kraken2_pe_wf	kraken2_db	File	workspace.kr
kraken2_pe_wf	read1	File	workspace.kraken2_standard_db
kraken2_pe_wf	read2	File	this.read2

Figure 34